POLIMAXX SP100

Acrylonitrile Butadiene Styrene IRPC Public Company Limited



Technical Data

Product Description SP100 is a super high impact grade of A	ABS resin for injection molding pro	ocess. It is suitable for auto parts (mo	torcycle component), refrigerator
handle, and electrical appliances where	need super high impact strength		
General			
Material Status	 Commercial: Active 		
Literature ¹	 Technical Datasheet (English 	n)	
UL Yellow Card ²	• E132283-222085		
Search for UL Yellow Card	 IRPC Public Company Limite 	ed	
Availability	Asia Pacific	Europe	North America
Features	Food Contact Acceptable	Ultra High Impact Resistance	
Uses	Appliance ComponentsAutomotive Applications	Electrical/Electronic ApplicationsHandles	
Agency Ratings	• FDA 21 CFR 181.32		
RoHS Compliance	RoHS Compliant		
Processing Method	Injection Molding		
Physical		Nominal Value Unit	Test Method
Melt Mass-Flow Rate (MFR) (220°C/10.	0 kg)	18 g/10 min	ASTM D1238
Mechanical		Nominal Value Unit	Test Method
Tensile Strength (Yield, 23°C)		44.1 MPa	ASTM D638
Flexural Modulus (23°C)		2160 MPa	ASTM D790
Flexural Strength (Yield, 23°C)		63.7 MPa	ASTM D790
Impact		Nominal Value Unit	Test Method
Notched Izod Impact (23°C, 6.35 mm)		330 J/m	ASTM D256
Hardness		Nominal Value Unit	Test Method
Rockwell Hardness (R-Scale, 23°C, 6.3	5 mm)	110	ASTM D785
Thermal		Nominal Value Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed, 6.35 mm		90.0 °C	
1.8 MPa, Unannealed, 6.35 mm		84.0 °C	
Flammability		Nominal Value Unit	Test Method
Flame Rating (1.5 mm)		НВ	UL 94
Injection		Nominal Value Unit	
Drying Temperature		80 to 85 °C	
Drying Time		2.0 to 5.0 hr	

Notes

Processing (Melt) Temp

190 to 240 °C



Form No. TDS-20792-en

¹ These links provide you with access to supplier literature. We work hard to keep them up to date; however you may find the most current literature from the supplier.

² A UL Yellow Card contains UL-verified flammability and electrical characteristics. UL Prospector continually works to link Yellow Cards to individual plastic materials in Prospector, however this list may not include all of the appropriate links. It is important that you verify the association between these Yellow Cards and the plastic material found in Prospector. For a complete listing of Yellow Cards, visit the UL Yellow Card Search.

³ Typical properties: these are not to be construed as specifications.

POLIMAXX SP100

Acrylonitrile Butadiene Styrene

IRPC Public Company Limited



Where to Buy

Supplier

IRPC Public Company Limited

Thailand

Telephone: +66-2-678-5000 Web: http://www.irpcmarket.com/

Distributor

API-Kolon Engineering Plastics

Telephone: 847-550-5556 Web: http://www.apikolon.com/

Availability: Mexico, North America, South America

Click Plastics AG

Click Plastics AG is a Pan European distribution company. Contact Click Plastics for availability of individual products by country.

Telephone: +49-6251-770-690-0 Web: http://www.clickplastics.com

Availability: Germany

PolySource

Telephone: 866-558-5300 Web: http://www.polysource.net/ Availability: North America

Resinal de México

Telephone: +52-55-5254-7600 Web: http://resinal.mx/ Availability: Mexico

Southland Polymers

Southland Polymers - Full Service Engineering and Commodity Resin Distribution Since 1979

Telephone: 562-921-0444

Web: http://www.southlandpolymers.com/

Availability: Central America, North America, South America

